SMART BUILD SANTA BARBARA (SB²) PROGRAM Application

Project Title:				
Agent/Architect's Na	me:			
Telephone:	Fax:	Email:		_
P&D Planner:		_		
Description of Projec	t: Please circle or fill in.			
a. Residentia	al/Nonresidential/Municip	al		
b. New / Ad	dition / Alteration			
c. Square Fo	otage:			
d. Landscap	e Plan Included?			
e. Briefly De	scribe Scope of Work:			_
				_
				_
				_
				_
Percent beyond Cali	fornia Energy-Efficient St	andards (Title 24):	%	
Percent of Building's	s Greenhouse Gas Emissio	on Reduction Above Baselii	ne:%	
Energy Points Total:				

SMART BUILD SANTA BARBARA (SB²) PROGRAM Tier Menu

Incentives Tier 1 • 50% Reduction in Energy Plan Check Fee • Exceed Title 24 Standards by 30% • Expedited Building & Safety Division Plan • Meet all CALGreen Mandatory Requirements • Residential - 50 Points Check Review Process (Average 30% – 50% Time Reduction) Nonresidential - 30 Points • Use of SB² Logo for Marketing Tier 2 **Incentives** • All Tier 1 incentives listed above Exceed Title 24 Standards by 40% Resolution of Commendation from the County • Meet all CALGreen Mandatory Requirements **Board of Supervisors** • Residential – 70 Points Nonresidential - 40 Points * Tiers are applicable to all new and existing residential and nonresidential developments. Please check off and list the energy-efficient features you are incorporating in your design to reach beyond California Energy-Efficient Standards (Title 24): Insulation for Walls, R-value: Solar Water Heating: _____ Solar Pool Heating: Insulation for Ceiling, R-value: Window/Glazing, U-value: Lighting: Gas Furnace, AFUE: Other: Air Conditioner, SEER:

Gas Water Heater, EFR:

Thermal Mass, Square Footage: _____

Energy Points Menu

The following points are for features not addressed in Title 24.

Energy Section

1	Photovoltaic and Wind Generators: 2 points for each 20% of project's electrical demand provided (e.g., provides 60% of demand = 6 points).	10 points max
2.	Solar pool heating	2 points
3.	Passive Cooling Strategies: passive cooling planned for or designed into structure (e.g.	1 point
	strategically sized overhangs or trellis on south side, movable awnings, operable skylights,	each;
	fan, thermal chimney, thermal mass, a cupola or roof opening for hot air venting, radiant	5 points
	barrier, or underground cooling tubes).	max
4.	Lighting	
	a) Residential: Whole-home, high efficiency, lighting control system with conditional logic	1 point
	b) Residential and non-residential: The preprogrammed demand response strategies should be capable of reducing the total lighting load by a minimum 30 percent through dimming control or bi-level switching.	1 point
	c) Outdoor lighting: These systems shall be designed and installed to comply with the following: 1. The minimum requirements in the California Energy Section 150(K) Table 150.C as defined in Chapter 10 of the California Administrative Code; and 2. Backlight,	1 point
	Uplight and Glare (BUG) ratings as defined in IESNA TM-15-11; and 3. Allowable BUG ratings not exceeding those shown in Table 5.106.8, or Comply with a local ordinance	
	lawfully enacted pursuant to Section 101.7, whichever is more stringent. Exceptions: 1. Luminaires that qualify as exceptions in Section 147 of the California Energy Code 2. Emergency lighting	
5	Water Heaters: located within 25 feet of main area of usage or use of hot water re-circulating	1 point
]].	system (either on demand or time and temperature controls).	ı polit
6.	Appliance Efficiency: need manufacturers spec. sheets for credit. All appliances must be	
	Energy Star rated and there is no second refrigerator. Appliances must be installed prior to occupancy.	1 point
7.	ethanol, biodiesel, etc.).	2 points
8.	Purchase off-site renewable energy sources (e.g., utility-based wind, PV, emissions credits, etc.). 1 points for each 20% of project's electrical demand provided (e.g., provides 60% of demand = 3 points).	5 points
9.	Use of air, water, and ground source heat pumps for space and water heating.	1 point
10	D. Create energy efficient fresh air supply (Energy Recovery Ventilation or Heat Recovery Ventilation).	1 point
13	1. Utilize a solar thermal system (and have back-up system in place)	1 point
	2. Design for passive heating strategies (e.g., southern windows in conjunction w/thermal mass,	1 point
	different type of glazing on the south side, higher SHGC coefficient for allowing better heat	Each
	gain, etc.). Specify type, location, and quantity of thermal mass.	4 points
		max
13	3. Design for efficient layout of electrical branch circuits and panel locations by placing a majority of branch circuits in the slab with the length from the panel to a receptacle 12 inches above the floor (may need additional plan check time).	1 point

Summer Shading and Wind Protection

(measures taken to increase energy efficiency)

	14. Summer Shading: substantial shading by moveable exterior awnings or trees by the west or	2 points
-	south elevations of the building. Tree on south elevation should be deciduous. (1 point for	
	each elevation). One additional point if done with existing trees. Plans must show existing	max
	trees.	
- 1	15. Protection of Building from Heat Loss:	
	a) planting a windbreak, earthen berm, or building a solid wall along the north or windward side of the building approximately 10 feet away and 2/3 of the building	1 point
	height.	
	b) building fin walls on the building or planting against the building to create an air envelope around the building.	1 point
- 1	16. Other quantifiable, site specific, energy efficient features approved by county representative.	10 points
		max
	Siting	
	(measures taken to reduce thermal breaks)	
1	17. New buildings: Locate building away from low spot of surrounding terrain to lower heating	1 point
	loads (may not apply to all projects due to topography).	
- -	18. If not implementing passive solar design, maximize wall area and minimize window area on	1 point
	south and east elevations.	
	19. Maximize roof orientation for future solar systems and include stub outs for future solar.	1 point
	19. Maximize roof orientation for future solar systems and include stub outs for future solar.20. New buildings: design for use of renewable energy sources available near the site (e.g., PV, solar hot water, wind, etc.).	1 point 1 point

Building Materials Section

21. Structure:	
a) advanced framing (24" on center), engineered wood products, engineered factory panelized built models, recycled content (50% minimum) materials (e.g. steel studs, etc.). 50% of total framing = 1 point, 60% = 2 points, 70% = 3 points, 80% plus = 4 points (may require additional plan check time)	· ·
b) use of innovative structural system for 50% or more of building walls: structural	4 points
insulating panels, insulating concrete forms, insulating block, straw bale, etc. 50% = 1 point, 60% = 2 points, 70% = 3 points, 80% plus = 4 points (may require additional plan check time)	max
22. Recycle Existing Buildings: 2 points for reusing 60% of existing buildings/building materials	4 points
onsite (or to be used at another site). An additional point for each 20% reuse of existing building/building materials beyond the 60%.	max
23. All insulation to include entire building and be 100% recycled content, wet blown, open/closed cellulose, or cellulose with UL fire retardant, to be coordinated with attic rafter venting.	1 point
24. Conditioned crawl spaces of a certain height (cannot be used as basement)	1 point

25. Exterior Building Envelope:	
a) Tri-County local masonry materials for stone work; 75% plus.	1 point
b) plaster or cementitious siding; 75% plus.	1 point
c) recycled content, salvaged, or certified sustainably harvested wood; 75% plus.	
d) roof: recycled-content roofing material or combination cement-fiber roofing and	1 point
minimum 30 year rated life on at least 50% of roof.	
e) roof: vegetated roof or high-emissivity roofing (may require additional plan check	1 point
time).	
26. Interior Materials and Finishes:	
a) floor: tile, ceramic tile, stone, finished concrete, cork or natural linoleum; recycled-	
content or natural-content carpet and pad (tacked); 75% plus.	1 point
28. Indoor Environmental Quality:	
a) create a whole house vacuum	1 point
b) use non-toxic, zero VOC paints	1 point
c) reduce exterior noise/noise attenuation	1 point
d) use minimum merv. 10 filters	1 point
e) install electrical cooking appliances that use no combustion gases	1 point
27. Other quantifiable, site specific, building material strategies approved by county	10 points
representative.	max
Non-Energy Related Building Techniques	
Non-Energy Related Ballating Techniques	
29. Water Conservation Measures:	
a) landscape with drip irrigation system or equivalent using drought tolerant or native	1 point
plants; 75% plus.	
b) create a plan to preserve on-site native vegetation; 75%.	1 point
c) design a greywater system, enhanced treatment system, or shallow drip dispersal	1 point
system in accordance with county regulations	
d) design a rainwater collection and reuse system	1 point
e) install dual-flush toilets	1 point
f) install waterless urinals	1 point
g) Use of permeable paving; 75% plus.	1 point
h) Reduce water usage versus baseline by 40%	1 point
i) Install showerheads with 1.5 gallons/minute (or less)	1 point
30. Implement a construction waste management plan to reuse and minimize material waste	1 point
that exceeds CALGreen requirements. (Applicant can obtain a form from SB ² Administrator)	
Commercial Specific	
32. Commercial/industrial developments that include the following facilities to reduce vehicular	11 points
trips during the work day: cafeterias (1 points), postal machines (1 point), automated bank	max
tellers (1 point), child care facilities (2 points), delivery services for employees (1 point),	
provide employee showers (1 point), provide company electric vehicles (1 point) and charge	
stations (1 point), provide company bikes (1 point), provide indoor employee bike racks (1	
point), gym (1 point).	
Energy Point Total Points	